

**DESCRIPTION**

Procedo PRO610 Spray Adhesive is a low odor, low VOC, non-flammable water based adhesive formulated for use with Procedo products. The immediate high sheer strength allows for foot traffic after installation and eliminates the worry of adhesive displacement due to early traffic. Procedo PRO610 Spray Adhesive reduces the amount of adhesive on projects by up to 80%, therefore reducing the amount of weight during shipment and manufacturing. The canisters are completely recyclable and the design allows for the complete use of the contents, so there is no waste.

**COLOR**

White

**PACKAGING**

22 ounce Aluminum Cans, 6 Cans per Case

**WEIGHT**

12 Pounds per Case

**TROWEL SIZE**

No Trowel Needed

**COVERAGE**

170 – 200 Square Feet per Can

**RECOMMENDED SUBSTRATES**

Recommended for properly prepared Concrete, Terrazzo, Wood, Metal and Fiberglass

**ADHESIVE WORKING TIME**

Flash Time: Approximately 15 – 20 Minutes or until no adhesive transfer to the finger when touched

Working Time: 2 Hours, protect open adhesive from dust contamination

**MOISTURE AND PH REQUIREMENTS**

ASTM F 1869; Calcium Chloride, 8.0 lbs  
ASTM F 2170; Relative Humidity, 90%  
pH; 11 or less

**PRODUCTS**

Versa Quartz Tile, Sylvana LVT

**CLEAN UP**

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol.

**VOC's**

0 Grams per Liter of Coating

**LIMITATIONS**

Maintenance, after 48 Hours

All Traffic, Immediately

Not for use over existing floor covering or old adhesives

Not for use outdoors

**SPRAY PATTERN**



**SHELF LIFE**

Shelf life is two years when stored at 70° F (21° C) in an unopened container

**FREEZE THAW STABILITY**

Protect material from freezing

**QUALIFICATIONS**

FloorScore, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from [www.procedoflooring.com](http://www.procedoflooring.com), emailing [technical@procedoflooring.com](mailto:technical@procedoflooring.com), or by contacting Procedo Customer Service.