

I – PRODUCT NAME


Procedo Wall Base

II – MANUFACTURER

Procedo Flooring
1401 East 6th Street
Tuscumbia, Alabama 35674
Phone: 866-955-8291
Fax: 419-436-4302
Website: www.procedoflooring.com

III – PRODUCT DESCRIPTION

ASTM F 1861, Type TP, Group 2, Styles B
Thermoplastic Rubber Formulation designed to meet or exceed the above-mentioned standard specification for Resilient Wall Base. Inside and Outside corners are available with a nominal 3” return.



Available in 48” Lengths and 120’ Coils

IV – TECHNICAL DATA

ASTM F 1861 – Resilient Wall Base, Type TP, Group 2, Style B
ASTM E 648 (NFPA 253), Critical Radiant Flux - Class 1
ASTM E 662 (NFPA 258), Smoke Density - Passes

V – PRODUCT LIMITATIONS

- Product is for indoor use only
- Not for installation on surfaces exposed to moisture or extreme temperature changes
- Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays
- Not to be used in direct contact with heat sources, such as radiators, hot ovens or other heated equipment

VI – INSTALLATION

Please refer to the Procedo Wall Base Installation documentation for complete detailed procedures.

Recommended Adhesives

- Mapei® ECO™ 575 Premium Wall Base Adhesive
- Parabond Fusion X Premium Wall Base Adhesive
- Henry® 440 Premium Wall Base Adhesive

VII – PRODUCT MAINTENANCE

Some disinfectants, cleaning agents, floor maintenance products and pesticides may stain or damage the surface of the Procedo Wall Base. Clean the wall base with a soft cloth dampened with a neutral pH cleaner and warm water solution. Rinse sparingly with water. If applying finish to flooring, take necessary precautions to keep finish from the Procedo Wall Base. If applying finish to the Procedo Wall Base, test inconspicuous area first for compatibility

VIII – AVAILABILITY, COST & SAMPLES

Products are available through Procedo Flooring appointed representatives. To locate the nearest representative, contact Customer Service at (866) 955-8291 or by email at support@procedoflooring.com

IX – TECHNICAL ASSISTANCE

Obtain product data, installation instructions or additional Technical Assistance by contacting your Procedo representative or Customer Service at (866) 955-8291 or by email at support@procedoflooring.com

X – LIMITED WARRANTY

Limited One (1) Year Manufacturers Warranty
Refer to www.procedoflooring.com to obtain complete Installation & Warranty information



1401 East 6th Street | Tuscumbia, AL 35674
Phone: 866.955.8291 | Fax: 419.436.4302
procedoflooring.com